


VARIANT VX 7729/160-4 HA

The three-knuckle hinge set for timber/aluminium entrance doors



A HINGE SYSTEM SPECIALLY DEVELOPED FOR TIMBER/ALUMINIUM ENTRANCE DOORS

Entrance doors made of timber and aluminium offer special advantages. The wood provides stability and safety with a look of cosiness from the inside. The aluminium cover fitted to the outside offers reliable protection against weathering plus extra stability. SIMONSWERK supports the trend towards timber/aluminium doors with a technically mature, elegant three-knuckle hinge solution.


The VARIANT VX 7729/160-4 HA MSTS has been specially developed on the basis of the proven VARIANT VX three-knuckle hinge technology. With a load capacity of up to 160 kg, it can be combined with the three-dimensionally adjustable receivers VX 7531 3D and VX 7535 3D. It also comes with a security pin, a welded hinge knuckle and concealed axial-radial slide bearing technology. This innovative door hinge made of satin brushed stainless steel constitutes an ideal combination of technical functionality with a modern, aesthetic look. It is available as a set consisting of hinge, receiver and cover angle.



VISIT OUR PRODUCTSELECTOR

At www.simonswerk.com you will find exact details and precise product descriptions, which will make it easier for you – as a manufacturer, distributor, specifier and planner – to choose the right hinge system.





NEW

VX 7729/160-4 HA SET

with welded hinge knuckle for unrebated, outward opening timber/aluminium doors

| | | |
|-------------------|------------------|---------------------|
| Door Hinge | unrebated | up to 160 kg |
|-------------------|------------------|---------------------|

Product features

- for unrebated timber/aluminium doors
- for 3D adjustable VARIANT VX receivers
- with security pin
- with welded hinge knuckle
- internal torsion-proof pin
- concealed, maintenance-free axial-radial slide bearings
- for timber frames

Technical details

| | | |
|--------------------|---|-------------|
| load capacity | i two hinges per door leaf (1 x 2 m) | 160,0 kg |
| knuckle length | | 160,0 mm |
| knuckle diameter | | 22,5 mm |
| material thickness | | 4,0 mm |
| screws | | 6,0x50,0 mm |

Finishes

satin stainless steel, further finishes on request

Combination

| | | |
|----------|-------------|------------|
| Receiver | block frame | VX 7531 3D |
| | blind frame | VX 7535 3D |


Note

i The load capacity mentioned above refers to the use of 2 hinges per door leaf (1x2m)



example receiver
VX 7531 3D

example cover angle
VX 7561 KK



Scope of supply

| | | |
|-------------------|-------------|-----------------------|
| Combination Set 1 | hinge | VX 7729/160-4 HA MSTS |
| | receiver | VX 7531 3D |
| | cover angle | VX 7561 KK |
| Combination Set 2 | hinge | VX 7729/160-4 HA MSTS |
| | receiver | VX 7531 3D |
| | cover angle | VX 7561 KR |

Further combinations on request

VISIT OUR PRODUCTSELECTOR ON:
www.simonswerk.com



SIMONSWERK GmbH

Bosfelder Weg 5
D-33378 Rheda-Wiedenbrück
Germany

Fon +49 (0)5242/413-0
Fax +49 (0)5242/413-260

sales@simonswerk.com
www.simonswerk.com

